

# AltoPlex C410

## 60GHz Outdoor Wireless Standard Client Unit

The C410 is a 60GHz radio with integrated 64-element beamforming antenna that enables the quick and easy installation of reliable, gigabit connections, all in a cost-effective and compact form factor.

The C410 is carrier-grade, manufactured in the USA and features IP67 weather-sealing for reliable operation outdoors and in harsh environments. It is ideally suited as a client for residential and enterprise gigabit access applications.



### High Capacity

Up to 2Gbps aggregate

### Low Latency

Sub 1ms latency

### Adaptive Beamforming

64-element, phased array, beamforming antenna with 90° azimuth and 40° elevation scanning for maximum link resiliency and ranges up to 820ft (250m) MCS-9

### Gigabit Ethernet

Built-in gigabit RJ45 port

### GPS Location

Easily locate the radio using the integrated GPS receiver.

### Dense Network Ready

60GHz spectrum with beamforming and TDMA for extremely reliable dense networks

### Security

AES 128 encryption with automatic secure key distribution

### Carrier-Grade

IP67 rated enclosure and built in USA for reliable, long-term operation in the field

### Simple and Rapid Installation

AltoWav's antennas auto-align for easy installs. Our Open API and native Layer 2 architecture enable easy integration into operators' existing networks

# Specifications

## SYSTEM

<b>Configuration</b>	Point-to-Point and Point-to-Multipoint Client
<b>Frequencies</b>	57 - 66GHz
<b>Channel Bandwidths</b>	4 non-overlapping 2.16GHz channels
<b>Channel Access</b>	TDMA/TDD
<b>Modulation and Coding Schemes</b>	12 levels, adaptive—MCS-0 (BPSK) to MCS-12 (16QAM)
<b>Antenna</b>	Integrated 64-element beamforming antenna with wide scanning range: 90° azimuth, 40° elevation
<b>Maximum EIRP</b>	37dBm
<b>Range</b>	Up to 820ft (250m) MCS-9
<b>Capacity</b>	Up to 2Gbps aggregate
<b>Ethernet Frame Type</b>	Transparent bridging of all Ethernet types including VLAN and VLAN stacking
<b>Latency</b>	< 1ms
<b>L2 switching</b>	Complete Layer 2 switching, including VLAN support
<b>Security</b>	AES 128
<b>Location</b>	Integrated GPS receiver to locate individual radios

## CONNECTIVITY

<b>Ethernet</b>	1 x 1GbE RJ45
<b>Voltage</b>	56VDC
<b>PoE Input</b>	802.3af
<b>Power Consumption</b>	10W maximum
<b>Included PoE Injector</b>	Indoor 802.3af (15W) 1GbE PoE injector with 2.6ft (0.8m) US power cord

## MANAGEMENT

<b>Management</b>	Web GUI, CLI, REST API and AltoCommand (optional)
-------------------	---

## MECHANICAL

<b>Dimensions (H x W x D)</b>	5.9" x 3.8" x 1.4" (150 x 95 x 35mm)
<b>Weight</b>	14oz (400g)
<b>Operating Temperature</b>	-40° to +131°F (-40° to +55°C) -22°F (-30°C) cold start
<b>Casing</b>	Die-cast powder-coated aluminum chassis with PC-ABS radome
<b>Ingress Protection</b>	IP67
<b>Regulatory</b>	FCC, IC
<b>ESD</b>	IEC EN 61000-4-2
<b>EMC</b>	IEC EN 61000-4-3
<b>Mounting</b>	Integrated wall and pole mount supporting .5" band clamps. Additional mounting accessories supporting elevation adjustment are available.

## INCLUDED ACCESSORIES

<b>AX-P-IN-AF-1G-US</b>	Indoor 802.3af (15W) 1GbE PoE injector with 0.8m US power cord
-------------------------	--

## ACCESSORIES

<b>AX-AW3-MT-WALL</b>	Wall standoff bracket that enables azimuth adjustment
<b>AX-AW3-EXT-MOUNT</b>	Extended range pole mounting kit for AltoPlex radios, enabling up to +60/-45° elevation adjustment
<b>AX-PSW-OD-4AT-4C25</b>	Outdoor 4 port PoE 2.5GbE switch
<b>AX-PSW-OD-MOUNT</b>	Pole mount bracket for Outdoor PoE switch