

# AltoPlex D621

## 60GHz Outdoor Wireless Network Distribution Unit

The D621 is a 60GHz radio with integrated 128-element beamforming antenna that provides best-in-class link resiliency and full capacity range in a very compact form factor. It supports PtMP and can be configured as either a distribution or client unit for maximum flexibility.

The D621 is carrier-grade, manufactured in the USA and features IP67 weather-sealing for reliable operation outdoors and in harsh environments.



### High Capacity

Up to 3.8Gbps aggregate

### Low Latency

Sub 1ms latency

### Adaptive Beamforming

128-element, phased array, beamforming antenna with 90° azimuth and 40° elevation scanning for maximum link resiliency and ranges up to 1312ft (400m) MCS-9

### 2.5 Gigabit Ethernet

Built-in 2.5GbE port for maximum throughput

### Wi-Fi Management and GPS Location

Connect locally using the Wi-Fi network interface to manage the radio directly. Easily locate the radio using the integrated GPS receiver.

### Dense Network Ready

60GHz spectrum with beamforming and TDMA for extremely reliable dense networks

### Security

AES 128 encryption with automatic secure key distribution

### Carrier-Grade

IP67 rated enclosure and built in USA for reliable, long-term operation in the field

### Simple and Rapid Installation

AltoWav's antennas auto-align for easy installs, and our Open API and native layer 2 architecture enable easy integration into operators' existing networks

# Specifications

## SYSTEM

<b>Configuration</b>	Point-to-Point and Point-to-Multipoint Distribution or Client
<b>Frequencies</b>	57 - 66GHz
<b>Channel Bandwidths</b>	4 non-overlapping 2.16GHz channels
<b>Channel Access</b>	TDMA/TDD
<b>Modulation and Coding Schemes</b>	12 levels, adaptive—MCS-0 (BPSK) to MCS-12 (16QAM)
<b>Antenna</b>	Integrated 128-element beamforming antenna with wide scanning range: 90° azimuth, 40° elevation
<b>Maximum EIRP</b>	40dBm
<b>Range</b>	Up to 1312ft (400m) MCS-9
<b>Capacity</b>	Up to 3.8Gbps aggregate
<b>Ethernet Frame Type</b>	Transparent bridging of all Ethernet types including VLAN and VLAN stacking
<b>Latency</b>	< 1ms
<b>L2 switching</b>	Complete Layer 2 switching, including VLAN support
<b>Security</b>	AES 128
<b>PtMP Remote Support</b>	Up to 15 client units +1 distribution node connection
<b>Wi-Fi Management Interface</b>	2.4GHz IEEE 802.11b/g/n wireless management interface (not a data access point)
<b>Location</b>	Integrated GPS receiver to locate individual radios

## CONNECTIVITY

<b>Ethernet</b>	1 x 2.5GbE RJ45
<b>Voltage</b>	56VDC
<b>PoE Input</b>	802.3at
<b>Power Consumption</b>	15W maximum

## MANAGEMENT

<b>Management</b>	Web GUI, CLI, REST API and AltoCommand (optional)
-------------------	---

## MECHANICAL

<b>Dimensions (H x W x D)</b>	5.9" x 3.8" x 1.4" (150 x 95 x 35mm)
<b>Weight</b>	14oz (400g)
<b>Operating Temperature</b>	-40° to +131°F (-40° to +55°C) -22°F (-30°C) cold start
<b>Ingress Protection</b>	IP67
<b>Regulatory</b>	FCC, IC
<b>ESD</b>	IEC EN 61000-4-2
<b>EMC</b>	IEC EN 61000-4-3
<b>Mounting</b>	Integrated wall and pole mount supporting .5" band clamps. Additional mounting accessories supporting elevation adjustment are available.

## ACCESSORIES

<b>AX-P-IN-AT-5G-US</b>	Indoor 802.3at (30W) 5GbE PoE injector with 0.8m US power cord
<b>AX-AW3-MOUNT</b>	Pole mounting kit for AltoPlex radios, enabling up to +20/-15° elevation adjustment
<b>AX-AW3-EXT-MOUNT</b>	Extended range pole mounting kit for AltoPlex radios, enabling up to +60/-45° elevation adjustment