

C410

60GHz Outdoor Wireless Client Unit

The C410 is a 60GHz radio with integrated 64-element beamforming antenna that enables the quick and easy installation of reliable, gigabit connections, all in a cost-effective and compact form factor.

The C410 is carrier-grade, manufactured in the USA and features IP67 weather-sealing for reliable operation outdoors and in harsh environments. It is ideally suited as a client for residential and enterprise gigabit access applications.



High Capacity

Up to 1Gbps symmetrical

Low Latency

Sub 1ms latency

Adaptive Beamforming

64-element, phased array, beamforming antenna with 90° azimuth and 40° elevation scanning for maximum link resiliency and ranges up to 200m (MCS9)

Gigabit Ethernet

Built-in gigabit RJ45 port

Dense Network Ready

60GHz spectrum with beamforming and TDMA for extremely reliable dense networks

Security

AES 128 encryption with automatic secure key distribution

Carrier-Grade

IP67 rated enclosure and built in USA for reliable, long-term operation in the field

Simple and Rapid Installation

Altowav's antennas auto-align for easy installs. Our Open API and native Layer 2 architecture enable easy integration into operators' existing networks

Specifications

SYSTEM

Configuration	Point to Point and Point to Multipoint Client
Frequencies	57 - 66 GHz
Channel Bandwidths	4 non-overlapping 2.16GHz channels
Channel Access	TDMA/TDD
Modulation and Coding Schemes	12 levels, adaptive—MCS-0 (BPSK) to MCS-12 (16QAM)
Antenna	Integrated 64-element beamforming antenna with wide scanning range: 90° azimuth, 40° elevation
Maximum Output Power to Antenna	20dBm
Range	Up to 200m (MCS9)
Capacity	Up to 1Gbps symmetrical
Ethernet Frame Type	Transparent bridging of all Ethernet types including VLAN and VLAN stacking
Latency	< 1 ms
L2 switching	Complete Layer 2 switching, including VLAN support
Security	AES 128

MECHANICAL

Dimensions (H x W x D)	5.9" x 3.8" x 1.4" (150 x 95 x 35mm)
Weight	14oz (400g)
Operating Temperature	-30° to +55°C
Ingress Protection	IP67
Regulatory	FCC, IC
ESD	IEC EN 61000-4-2
EMC	IEC EN 61000-4-3

CONNECTIVITY

Ethernet	1 x 1GbE RJ45
Voltage	56VDC
PoE Input	802.3af
Power Consumption	10W maximum

MANAGEMENT

Management	Web GUI, CLI, REST API and Altowav Edge Controller (optional)
-------------------	---